




PROTEGRA CS RO

MEETING ALL PURE WATER DEMANDS



Laboratory, medical and industrial applications all need pure water in various qualities and quantities. The Protegra CS™ RO Series produces pure water for a wide variety of applications by reversing the natural osmosis process to deionize water in an environmentally friendly manner. Pure water produced via reverse osmosis can be put to a number of uses in laboratories – for rinsing laboratory glassware or as feed water to autoclaves, climatized cabinets and ultrapure water systems.

The Protegra CS™ RO Series focuses on economic efficiency, combining a compact design with high quality components and intelligent controls. The quality of the pure water produced depends on the quality of the inlet water entering the system.

The Protegra CS™ RO Series series is designed to produce large amounts of purified water with conductivity values depending on the salt content of the feed water (for example 1000 S/cm tap water quality: < 20 S/cm product water). The deionization rate is at least 98 %. Additional equipment, such as different tank sizes and pressure pumps, can be added to the plant according to customers' individual needs. The system can, for instance, be set up as a central water treatment plant with in a building and supplemented with accessories to form a closed circuit pipeline.

All systems are equipped with an RS 232 interface.

We would be happy to recommend the right system for you!

Typical Applications

- Feed for laboratory ultrapure water systems
- General chemistry
- Laboratory washing machines
- Water for autoclaves and environmental chambers
- Buffer preparation

Specifications Cabinet Version

		Protegra CS RO 200	Protegra CS RO 500	Protegra CS RO 750	Protegra CS RO 1000
Flow rate @ 15°C	l/h	200	500	750	1000
Rejection rate min.	%	98	98	98	98
Recovery rate max.	%	75	75	75	75
Operating pressure max.	bar	14	14	14	14
Power consumption	kW/h	0,55	0,55	1,6	1,6
Dimensions H/W/D	mm	1650x600x550	1650x600x550	1650x600x550	1650x600x750
Catalog number		W3T199617	W3T197521	W3T199222	W3T199821

Systems with higher flow rate on request

Specifications Frame Version

		Protegra OF RO 200	Protegra OF RO 500	Protegra OF RO 750	Protegra OF RO 1000
Flow rate @ 15°C	l/h	200	500	750	1000
Rejection rate min.	%	98	98	98	98
Recovery rate max.	%	75	75	75	75
Operating pressure max.	bar	14	14	14	14
Power consumption	kW/h	0,55	0,55	1,6	1,6
Dimensions H/W/D	mm	1640x605x600	1640x605x600	1640x605x600	1850x800x700
Catalog number		W3T269403	W3T314581	W3T314582	W3T314583

Systems with higher flow rate on request